Product data sheet Characteristics

8751011000

MD10B Damper Actuator, 2 Position, Non-Spring Return, 230 Vac, 1 m Leads, 10 Nm, IP54, Opt SPDT



Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MD
Actuator model	MD10B-230
Product destination	Dampers
Actuator	Rotary
Control type	Automatic reset
[Us] rated supply voltage	230 V AC
Transformer rated power in VA	5.5 VA
Power consumption in W	2.5 W
Power consumption in VA	2.5 VA AC
Hold-in power consumption in W	0.6 W
Hold-in power consumption in VA	5.5 VA AC
Control signal	2-position (on/off)
Power loss return	Non-spring return
Stroke auto calibration	False
Electrical insulation class	Class II
Tightening torque	88 lb.in
	10 N.m
Position indicator	Visual indicator with position ring
Lead length	1 m
Actuator rotation	95 °
Rotational range adjustment	95° maximum (limited by an adjustable end stop)
Stroke running time	150 S
IP degree of protection	IP43
Ambient air temperature for operation	-3050 °C
Relative humidity	095 % RH, non-condensing
Ambient air temperature for storage	-4080 °C
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	810.0 G
Package 1 Height	6.4 Cm
Package 1 width	11.2 Cm
Package 1 Length	18.7 Cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	

Product Life Status : Commercialised