



Main

Product or component type	Actuator
Actuator type	Thermoelectric
Product destination	Zone valves
Actuator	Linear
Control type	Manual override with 5/32 allen wrench
[Us] rated supply voltage	110...230 V AC
Power consumption in W	2 W
Hold-in power consumption in VA	2 VA AC
Control signal	2-position (on/off)
Power loss return	Spring return
Stroke length	4 Mm
Stroke auto calibration	False
Force N	140 N
Force lbf	32 Lbf
Position indicator	Stroke indicator on bracket
Connection valve	Coupling ring M30 x 1.5
Lead length	1.5 m
Leads and connections	Bipolar
IP degree of protection	IP44
Ambient air temperature for operation	2...50 °C
Relative humidity	5...95 % non-condensing
Ambient air temperature for storage	-45...60 °C
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	200.0 G
Package 1 Height	5.5 Cm
Package 1 width	10 Cm
Package 1 Length	13 Cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Product Life Status : **Commercialised**