



Main

Range	EcoStruxure Building Expert
Product name	SE7000 Series
Device short name	SE7305
Product or component type	Room controller
Device application	Low voltage fan coil
PIR cover	Without cover
Sensor type	10 kOhm T2 NTC thermistor measurement range: +/- 0.2 °F

Complementary

Range compatibility	EcoStruxure Building Expert communication card EcoStruxure Building Expert sensor EcoStruxure Building Expert temperature sensor EcoStruxure Building Expert relay EcoStruxure Building Expert sensor coverplate
[Us] rated supply voltage	10...30 V AC 50/60 Hz
Rated operational power in VA	2 VA
Electrical insulation class	Class II
Network frequency	60 Hz 50 Hz
Communication port protocol	LonWorks
Information displayed	Temperature: - 40...122 °F
Control accuracy	Temperature: +/- 0.9 °F, (at 70 °F typically calibrated)
Number of inputs	1 dry contact
Number of outputs	2 universal
Output type	Triac
Output rating	30 V AC, 1 A (maximum) 30 V AC, 3 A (inrush)
Temperature setting range	4...32 °C heating

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	-17 °C per step 12...38 °C cooling
AWG gauge	AWG 22...AWG 18
Connections - terminals	Screw terminal
Width	86.87 mm
Depth	29.97 mm
Height	124.97 mm
Net weight	0.34 kg

Environment

Setting range	Humidification: 10...90 % Dehumidification: 15...95 %
Ambient air temperature for operation	-0...50 °C
Ambient air temperature for storage	-30...50 °C
Relative humidity	0...95 % non-condensing
Standards	FCC part 15 subpart B UL 873 ICES-003 CSA C22.2 No 24
Product certifications	CE C-Tick conforming to AS/NZS CISPR 22 FCC conforming to CFR 47 part 15 class A UL listed file E27734 CCN XPAX UL listed file E27734 CCN XPAX7
Directives	89/336/EEC - electromagnetic compatibility

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	200 g
Package 1 Height	5.1 cm
Package 1 width	10.1 cm
Package 1 Length	15.2 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins