# Product data sheet Characteristics

# SE7355C5045W

EBE - FCU controller - Zigbee - lodging - RH sensor - floating



#### Main

Range	EcoStruxure Building Expert	
Product name	SE7000 Series	
Device short name	SE7305	
Product or component type	Room controller	
Device application	Low voltage fan coil	
PIR cover	Without cover	-
Sensor type	Single point calibrated bulk polymer RH sensor measurement range: +/- 5 % 10 kOhm T2 NTC thermistor measurement range: +/- 0.2 °F	

## Complementary

Range	EcoStruxure Building Expert	
Product name	SE7000 Series	
Device short name	SE7305	
Product or component type	Room controller	
Device application	Low voltage fan coil	
PIR cover	Without cover	
Sensor type	Single point calibrated bulk polymer RH sensor measurement range: +/- 5 % 10 kOhm T2 NTC thermistor measurement range: +/- 0.2 °F	
Complementary		
Range compatibility	EcoStruxure Building Expert communication card EcoStruxure Building Expert sensor EcoStruxure Building Expert temperature sensor EcoStruxure Building Expert relay EcoStruxure Building Expert sensor coverplate	
[Us] rated supply voltage	1030 V AC 50/60 Hz	
Rated operational power in VA	2 VA	
Electrical insulation class	Class II	
Network frequency	60 Hz 50 Hz	
Communication port protocol	Zigbee	
Function available	Humidity control	
Information displayed	Temperature: - 40122 °F	
Control accuracy	Humidity: +/- 5 %, 2080 % RH (non-condensing) Temperature: +/- 0.9 °F, (at 70 °F typically calibrated)	
Number of inputs	1 dry contact	
Number of outputs	2 universal	
Output type	Triac	
Output rating	30 V AC, 1 A (maximum) 30 V AC, 3 A (inrush)	
Temperature setting range	432 °C heating -17 °C per step 1238 °C cooling	

AWG gauge	AWG 22AWG 18
Connections - terminals	Screw terminal
Width	86.87 mm
Depth	29.97 mm
Height	124.97 mm
Net weight	0.34 kg

### Environment

Setting range	Humidification: 1090 % Dehumidification: 1595 %
Ambient air temperature for operation	-050 °C
Ambient air temperature for storage	-3050 °C
Relative humidity	095 % non-condensing
Standards	ICES-003 UL 873 CSA C22.2 No 24 FCC part 15 subpart C
Product certifications	CE C-Tick conforming to AS/NZS CISPR 22 UL listed file E27734 CCN XPAX UL listed file E27734 CCN XPAX7 FCC
Directives	89/336/EEC - electromagnetic compatibility

#### Packing Units

r doming ormo	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	200 g
Package 1 Height	10 cm
Package 1 width	15 cm
Package 1 Length	5 cm