Product data sheet Characteristics

SE7652B5545E

EBE - RTU controller - LonWorks - scheduling +PIR cover - 2H/2C



Main

Range	EcoStruxure Building Expert	÷
Product name	SE7000 Series	
Device short name	SE7600B	
Product or component type	Room controller	
Device application	Low voltage rooftop	- i
Product specific application	2-stage cooling 2-stage heating	tipouc
Sensor type	10 kOhm T2 NTC thermistor measurement range: +/- 0.2 °F	
PIR cover	With cover	

Complementary

Complementary		
Range compatibility	communication card sensor temperature sensor relay sensor coverplate	
[Us] rated supply voltage	1030 V AC 50/60 Hz	
Rated operational power in VA	2 VA	
Electrical insulation class	Class II	
Network frequency	60 Hz 50 Hz	
Communication port protocol	Without	
Function available	Scheduling	
Temperature setting range	432 °C heating -17 °C per step 1238 °C cooling	
Information displayed	Temperature: - 40122 °F	
Control accuracy	Temperature: +/- 0.9 °F, (at 70 °F typically calibrated)	
Number of inputs	2 dry contact	
Number of outputs	2 universal	
Output rating	For digital output: 30 V AC, 1 A (maximum) For digital output: 30 V AC, 3 A (inrush) For analog output: 010 V DC, <= 5 mA into >= 2 kOhm	

Proportional band	For heating: adjustable P regulator by -17 °C (factory setting) For cooling: adjustable P regulator by -17 °C (factory setting)	
Contact operation	5 standard push-button	
AWG gauge	AWG 22AWG 18	
Connections - terminals	Screw terminal	
Width	86.87 mm	
Depth	29.97 mm	
Height	124.97 mm	
Net weight	0.34 kg	

Environment

Relative humidity	095 %, non-condensing (operating) 095 %, non-condensing (storage)
Ambient air temperature for operation	-050 °C
Ambient air temperature for storage	-3050 °C
Standards	FCC part 15 subpart B UL 873 CSA C22.2 No 24 ICES-003
Product certifications	FCC conforming to CFR 47 part 15 class A CE C-Tick conforming to AS/NZS CISPR 22 UL listed file E27734 CCN XPAX UL listed file E27734 CCN XPAX7
Directives	89/336/EEC - electromagnetic compatibility

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	500 g	
Package 1 Height	10 cm	
Package 1 width	15 cm	
Package 1 Length	5 cm	