



### Main

Range	SpaceLogic
Product name	SmartX Living Space Sensor
Product or component type	Sensor coverplate
Device presentation	Cover plate

### Complementary

Device application	HVAC
Supply	Base
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers EcoStruxure Building Operation SmartX Living Space Sensor base unit
Material	ABS (acrylonitrile butadiene-styrene)
Colour	White
Surface finish	Matt
Connections - terminals	Bus terminal (back)
Width	85 mm
Depth	20 mm
Height	115 mm

### Environment

Relative humidity	0...95 %
Ambient air temperature for operation	0...50 °C
Standards	UL 916 FCC part 15 class B
Product certifications	CE conforming to EN 61000-6-3 RCM EAC ICES-003
IP degree of protection	IP20
Flame retardance	UL94-V0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

**Offer Sustainability**

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>