



Main

Range	SpaceLogic
Product name	SmartX Living Space Sensor
Product or component type	Sensor coverplate
Device presentation	Cover plate
Sensor type	PIR sensor

Complementary

Device application	HVAC Temperature control Fan speed controller
[Us] rated supply voltage	24 V DC
Supply	Base
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers EcoStruxure Building Operation SmartX Living Space Sensor base unit
Function available	Override switches Setpoint adjustment Blind control Light control
Movement detection area	4 m at 140° (1.35 m mounting) 5 m of radius (wall) at 110° (1.35 m mounting) 6 m at 60° (1.35 m mounting)
Material	ABS (acrylonitrile butadiene-styrene)
Colour	White
Surface finish	Matt
Control type	tactile
Display type	Colour touchscreen
Display size	2.4 inch
Display resolution	320 x 240 pixels
Connections - terminals	Bus terminal (back)
Width	85 mm
Depth	20 mm
Height	115 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Relative humidity	0...95 %
Ambient air temperature for operation	0...50 °C
Standards	UL 916 FCC part 15 class B
Product certifications	CE conforming to EN 61000-6-3 RCM EAC ICES-003
IP degree of protection	IP20
Flame retardance	UL94-V0

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information